RNAV (GPS) Y RWY 7L

LOS ANGELES INTL (LAX)

WAAS	APP CRS	Rwy Idg	11259
CH 42504	071°	TDZE	128
W07A		Apt Elev	128

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 5°C (41°F) or above 54°C (130°F). DME/DME RNP -0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations. Simultaneous approach authorized.

MALSR

MISSED APPROACH: Climb to 3000 direct FILBA and on track 072° to DOWNE and hold.

D-ATIS	SOCAL APP CON				LOS ANGELES TOWER	GND CON		CLNC DEL	CPDLC
ARR 133.8	124.3	363.2	124.9	269.0	N 133.9	239.3	N 121.65	327.0	120.35	
DEP 135.65	(APCH FM WEST)		(090°-224°)		S 120.95	379.1	S 121.75	327.0	327.0	
	124.5	235.975	128.5	360.7			W 121.4	327.0		
	(225°-044°)		(045°-089°)							



ELEV 128	D	TDZE 128



CATEGORY	A	B	C	D
LPV DA	344/18 216 (300-½)			
LNAV/VNAV DA	464/30 336 (400-⅝)			
LNAV MDA	560/24 432 (500-½)		560/40 432 (500-¾)	



TDZ/CL Rwys 6R, 7L, 24R, and 25L
HIRL all Rwys

SW-3, 18 APR 2024 to 16 MAY 2024
SW-3, 18 APR 2024 to 16 MAY 2024