WAAS	APP CRS	Rwy Idg	5904
CH 70609	288°	TDZE	91
W28A		Apt Elev	99

RNAV (GPS) RWY 28R

MODESTO CITY-COUNTY-HARRY SHAM FLD (MOD)

RNP APCH.

T A For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C or above 54°C. For inoperative ALS, increase LNAV/VNAV all Cats visibility to ⅞ SM.

MALSR A5

MISSED APPROACH: Climb to 500 then climbing left turn to 3000 direct SHELI and hold, continue climb-in-hold to 3000.

ATIS	NORCAL APP CON	MODESTO TOWER ★	GND CON	UNICOM
127.7	120.95 269.45	125.3 (CTAF) L 257.8	121.7	122.95



ELEV 99 D TDZE 91



REIL Rwy 10L L
MIRL Rwy 10R-28L
HIRL Rwy 10L-28R L



CATEGORY	A	B	C	D
LPV DA	291-½ 200 (200-½)			
LNAV/VNAV DA	393-½ 302 (300-½)			
LNAV MDA	480-½ 389 (400-½)		480-⅝ 389 (400-⅝)	
C CIRCLING	540-1 441 (500-1)	600-1 501 (600-1)	700-1¾ 601 (700-1¾)	820-2¼ 721 (800-2¼)

SW-2, 18 APR 2024 to 16 MAY 2024
SW-2, 18 APR 2024 to 16 MAY 2024