LOC/DME I-SJC	APP CRS		30L	30R
110.9	306°	Rwy Idg	7614	7597
Chan 46		TDZE	57	55
		Apt Elev	62	62

ILS or LOC RWY 30L

NORMAN Y MINETA SAN JOSE INTL (SJC)

RNAV 1-GPS or RADAR required for procedure entry. DME required. From BORED: RNAV 1-GPS required.

T A # RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR Rwy 30L

MISSED APPROACH: Climb to 1900 on SJC VOR/DME R-303 to ARTAQ INT/SJC 7 DME and hold.

D-ATIS	NORCAL APP CON	SAN JOSE TOWER ★	GND CON	CLNC DEL	CPDLC	UNICOM
126.95	120.1 290.25	124.0 (CTAF) L 257.6	121.7	118.0		122.95

ARTAQ INT SJC 7

126° 30° 113.9 OSI R-053 Chan 86 R-303

LOCALIZER 110.9 I-SJC Chan 46

SAN JOSE 114.1 SJC Chan 88

ALTERNATE MISSED APCH FIX

R-300 120° 300°

OAKLAND OAK 116.8 Chan 115

Procedure NA for arrivals at BORED on V301 southeast bound and T333 northeast bound.

(IAF) BORED

5200 22° (10.4)

FORUL I-SJC 4.2

HIVAK I-SJC 9.6

JENES I-SJC 11.6

ZULUP I-SJC 13.4

(IF)

(IAF) KLIDE I-SJC 16.7 4000 230K

SWIGS

MSA SJC 25 NM 5600

400° 22° (4.4)

306° (3.3)

126°

ELEV 62 D TDZE 30L 57 TDZE 30R 55

TWR 12L 30R 11000 X 150 0.3% DOWN 0.3% DOWN

129 306°

REIL Rwy 12L

HIRL Rwys 12L-30R and 12R-30L L

1900 SJC R-303 ARTAQ INT

*LOC only

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 70).

FORUL I-SJC 4.2 HIVAK I-SJC 9.6 JENES I-SJC 11.6 ZULUP I-SJC 13.4 KLIDE I-SJC 16.7

*I-SJC 3 I-SJC 1.4

2700 3200 3600 4000 306°

1000* 2700

GS 3.00° TCH 54

1.6 NM 1.2 NM 5.3 NM 2 NM 1.8 NM 3.3 NM

CATEGORY	A	B	C	D
S-ILS 30L #	257/24 200 (200-½)			
S-LOC 30L	640/24 583 (600-½)		640-1¼ 583 (600-1¼)	
SIDESTEP 30R	640-1 585 (600-1)		640-1¾ 585 (600-1¾)	640-2 585 (600-2)

SW-2, 18 APR 2024 to 16 MAY 2024
SW-2, 18 APR 2024 to 16 MAY 2024